


DG M TNS 150 (952 403)


- Prewired complete unit consisting of a base part and plug-in protection modules
- High discharge capacity due to heavy-duty zinc oxide varistors/spark gaps
- High reliability due to "Thermo Dynamic Control" SPD monitoring device



Figure without obligation



Basic circuit diagram DG M TNS 150



Dimension drawing DG M TNS 150

Modular surge arrester for use in TN-S systems

Type	DG M TNS 150
Part No.	952 403
SPD according to EN 61643-11	Type 2
SPD according to IEC 61643-1/-11	Class II
Nominal a.c. voltage (U_N)	120/240 V
Max. continuous operating a.c. voltage (U_C)	150 V
Nominal discharge current (8/20 μ s) (I_n)	15 kA
Max. discharge current (8/20 μ s) (I_{max})	40 kA
Voltage protection level (U_P)	≤ 0.7 kV
Voltage protection level at 5 kA (U_P)	≤ 0.55 kV
Response time (t_A)	≤ 25 ns
Max. mains-side overcurrent protection	125 A gL/gG
Short-circuit withstand capability for max. mains-side overcurrent protection	50 kA _{rms}
Temporary overvoltage (TOV) (U_T)	175 V / 5 sec.
TOV characteristic	withstand
Operating temperature range (T_U)	-40°C...+80°C
Operating state/fault indication	green / red
Number of ports	1
Cross-sectional area (min.)	1.5 mm ² solid/flexible
Cross-sectional area (max.)	35 mm ² stranded/25 mm ² flexible
For mounting on	35 mm DIN rails acc. to EN 60715
Enclosure material	thermoplastic, red, UL 94 V-0
Place of installation	indoor installation
Degree of protection	IP 20
Capacity	4 module(s), DIN 43880
Approvals	KEMA, UL
Weight	417 g
Customs tariff number	85363030
GTIN	4013364128569
PU	1 pc(s)

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.