


SFL PRO 6X (909 250)

- Surge protection with monitoring device and disconnecter
- Interference suppressor filter
- Visual operating state (green) and fault indication (red)



Figure without obligation



Basic circuit diagram SFL PRO 6X



Dimension drawing SFL PRO 6X

Surge protective multiple socket outlet with mains filter

Type	SFL PRO 6X
Part No.	909 250
SPD according to EN 61643-11	Type 3
SPD according to 61643-1/-11	Class III
Nominal a.c. voltage (U_N)	230 V
Max. continuous operating a.c. voltage (U_C)	255 V
Nominal load current a.c. (I_L)	16 A
Nominal discharge current (8/20 μ s) (I_n)	3 kA
Total discharge current (8/20 μ s) [L+N-PE] (I_{total})	5 kA
Combined impulse (U_{OC})	6 kV
Combined impulse [L+N-PE] ($U_{OC total}$)	10 kV
Voltage protection level (U_P)	≤ 1.5 kV
Response time [L-N] (t_A)	≤ 25 ns
Response time [L/N-PE] (t_A)	≤ 100 ns
Max. mains-side overcurrent protection	16 A gL/gG or B 16 A
Short-circuit withstand capability for mains-side overcurrent protection with 16 A gL/gG	1.5 kA _{rms}
Temporary overvoltage (TOV) [L-N] (U_T)	335 V / 5 sec.
Temporary overvoltage (TOV) [L/N-PE] (U_T)	400 V / 5 sec.
Temporary overvoltage (TOV) [L+N-PE] (U_T)	1200 V + U_{CS} / 200 ms
TOV characteristic [L-N]	withstand
TOV characteristic [L/N-PE]	withstand
TOV characteristic [L+N-PE]	safe
Fault indication	red light
Operating state indication	green light
Number of ports	2
Operating temperature range (T_U)	-20°C...+40°C
Connecting cable	approx. 2000 mm
Number of socket outlets	6
For mounting on	plug-in systems with earth contact according to DIN 49440 / DIN 49441
Enclosure material	thermoplastic, black/silver, UL 94 V-1
Place of installation	indoor installation
Degree of protection	IP 20
Dimensions	571 x 72 x 43 mm
Mains filter	acc. to EN 60939-1
Attenuation for f = 1 MHz, balanced	≥ 32 dB
Attenuation for f = 1 MHz, unbalanced	≥ 30 dB
Weight	1,1 kg
Customs tariff number	85369010
GTIN	4013364132566
PU	1 pc(s)

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.