


## DB M 1 320 FM (961 135)


- Coordinated spark-gap-based lightning current arrester consisting of a base part and plug-in protection module
- Maximum system availability due to RADAX Flow follow current limitation
- Without additional cable length directly coordinated with DEHNguard surge protective device



Figure without obligation



Basic circuit diagram DB M 1 320 FM



Dimension drawing DB M 1 320 FM

Coordinated modular single-pole lightning current arrester with high follow current limitation; with remote signalling contact for the monitoring system (floating changeover contact)

Type	DB M 1 320 FM
Part No.	961 135
SPD according to EN 61643-11	Type 1
SPD according to IEC 61643-1/-11	Class I
Max. continuous operating a.c. voltage ( $U_c$ )	320 V
Lightning impulse current (10/350 $\mu$ s) ( $I_{imp}$ )	25 kA
Specific energy (W/R)	156.25 kJ/ohms
Nominal discharge current (8/20 $\mu$ s) ( $I_n$ )	25 kA
Voltage protection level ( $U_p$ )	$\leq 2.5$ kV
Follow current extinguishing capability a.c. ( $I_{fi}$ )	50 kA <sub>rms</sub>
Follow current limitation/Selectivity	no tripping of a 32 A gL/gG fuse up to 50 kA <sub>rms</sub> (prosp.)
Response time ( $t_a$ )	$\leq 100$ ns
Max. backup fuse (L) up to $I_K = 50$ kA <sub>rms</sub> ( $t_a \leq 0.2$ s)	315 A gL/gG
Max. backup fuse (L) up to $I_K = 50$ kA <sub>rms</sub> ( $t_a \leq 5$ s)	315 A gL/gG
Max. backup fuse (L) for $I_K > 50$ kA <sub>rms</sub>	200 A gL/gG
Max. backup fuse (L-L')	125 A gL/gG
Temporary overvoltage (TOV) ( $U_T$ )	440 V / 5 sec.
TOV characteristic	withstand
Operating temperature range (parallel connection) ( $T_{UP}$ )	-40°C...+80°C
Operating temperature range (series connection) ( $T_{US}$ )	-40°C...+60°C
Operating state/fault indication	green / red
Number of ports	1
Cross-sectional area (L/N, L'/N', N/PE (N)) (min.)	10 mm <sup>2</sup> solid/flexible
Cross-sectional area (L/N, N/PE(N)) (max.)	50 mm <sup>2</sup> stranded/35 mm <sup>2</sup> flexible
Cross-sectional area (L'/N') (max.)	35 mm <sup>2</sup> stranded/25 mm <sup>2</sup> flexible
For mounting on	35 mm DIN rails acc. to EN 60715
Enclosure material	thermoplastic, red, UL 94 V-0
Place of installation	indoor installation
Degree of protection	IP 20
Capacity	2 module(s), DIN 43880
Approvals	UL, CSA
Type of remote signalling contact	changeover contact
a.c. switching capacity	250 V/0.5 A
d.c. switching capacity	250 V/0.1 A; 125 V/0.2 A; 75 V/0.5 A
Cross-sectional area for remote signalling terminals	max. 1.5 mm <sup>2</sup> solid/flexible
Weight	330 g
Customs tariff number	85363030
GTIN	4013364118645
PU	1 pc(s)

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.